



RUBBERFLEX SDN.BHD. (Co. NO. 134208-U)

(Manufacturer of Quality Latex Thread)

Head Office: 21st Floor, U.B.N Tower, Box No 48, No. 10 Jalan P. Ramlee, 50250 Kuala Lumpur, Malaysia.

G.P.O.: Box 11218, 50740 Kuala Lumpur Malaysia. Tel: (603) 20720011 Fax: (603) 20785103

Website: www.rubberflex.com.my Email: info@rubberflex.com.my

Bare Extruded Natural Rubber Thread SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Bare Extruded Natural Rubber (Talc/Silicone Coated)
Company Name:	Rubberflex Sdn Bhd 21st Floor, UBN Tower, Jalan P. Ramlee Box No. 48, 50250, Kuala Lumpur, Malaysia
Telephone No.:	00-603-20720011
Fax No.:	00-603-20785103
Product Name	Bare Extruded Natural Rubber
Chemical Family	Natural Rubber (cis 1,4 polyisoprene)
Packing:	10-45 kg packing/box
Emergency Telephone No.:	00-603-20720011

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Contents:

- Natural Rubber
- Rubber Accelerator
- Rubber Stabiliser
- Antioxidant
- Vulcanizing Agent
- Vulcanizing Activators
- Fillers
- Anti-tack

SECTION 3: HAZARDS IDENTIFICATION

Classification of the substance
according to Directive 67/548/EEC
or Directive 1999/45/EC:

Labeling according to EU guidelines:

IATA/ICAO HAZARD RATING:

D.O.T. Rating: Not restricted

Risk phrases: Not restricted

Safety phrases:

SECTION 4: FIRST AID MEASURES

General information:

Stability: Stable

After inhalation:

After skin contact:

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Foam, carbon dioxide and water

Special hazards arising from the
substance:

Protective equipment: Not necessary

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions:

Environmental precautions:

Methods and material for
containment and cleaning up

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:

Fire and explosion protection:

Requirements to be met by storeroom: Keep away from sunlight, heat and petroleum products. Store at room and receptacles: temperatures. Avoid freezing conditions.

Information about storage in one common storage facility:

Further information about storage conditions:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities;

Ingredients with limit values that require monitoring at the work place:

Personal protective equipment:

General protective and hygienic measures; Wash hands with soap after handling.

Respiratory protection: Wear respiratory protection if ventilation is inadequate.

Protection of eyes:

Protection of hands/skin:

This product should not be handled by people who are allergic to natural rubber latex, nor should it come into contact with people who are sensitive to latex.

For those people who are unaware of their sensitivity, it is advised that they should discontinue handling. Symptoms include rashes, itching, sensation of burning, and appearance of bruising, breathing difficulties.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Packed in 20-50 kg boxes and neatly layered ribbon form either in talc or silicone coating.

Form: Single rubber strands fused together in ribbon form

Colour: White, black and cream.

Odor: Latex rubber

pH value

Melting point: n/a

Boiling point: n/a

Flash point: na

Flammability (solid, gaseous)

Ignition temperature:

Self-igniting:

Danger of explosion:

Explosion limits:

Vapor pressure at 20°C

Density:

Breaking point:

Elongation ratio:

Solubility in water:

Segregation coefficient (n-octanol/water):

Viscosity:

Dynamic:

Kinematic:

Solvent content:

Solids content:

SECTION 10: STABILITY AND REACTIVITY

Thermal decomposition/conditions to be avoided:
Incompatibility/Materials
Hazardous Decomposition products:

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity:
Primary irritant effect
On the skin:
On the eyes:
Sensitization:
Additional toxicological information:

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity:
Persistence and degradability:
Behavior in environmental systems:
Bio-accumulative potential
Ecotoxicological effects:

SECTION 13: DISPOSAL CONSIDERATION

General methods: Dispose of in accordance with local regulations.
Disposal methods:
Disposal of packaging: Contaminated packaging must be disposed of in the same manner as the product.
Non-contaminated packaging may be recycled. Contact your local services provider for more information.

SECTION 14: TRANSPORTATION INFORMATION

General:
UN Number:
Transport hazard class:
Packing group:
Environmental Hazards:
Special precautions for user:

SECTION 15: REGULATORY INFORMATION

Labeling:
Hazard designation product:
Transport hazard class:
Hazard component labeling:
Risk phrases:
Safety phrases: Discontinue handling in the event of skin irritation or rash. Avoid eye contact.
Special labeling:

SECTION 16: OTHER INFORMATION

Issued by: Health and Safety
Revision date:

Disclaimer:

These information are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. User is advised to evaluate the fitness or suitability of our product for their own use and Rubberflex Sdn Bhd will not be responsible for any damages/claims arising from these data.

Safety data sheet

(According to Regulation (EC) 1907/2006)

 **Recron**
Malaysia Sdn Bhd
Member Reliance Group

Recron Polyester Texturised Yarn

1. IDENTIFICATION OF SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

1.1 Identification of the product:

Product name: **Recron Polyester Texturised Yarn**
Product types: Recron-Semidul I, Recron-Bright, Recron- Cationic

1.2 Use of the product: *Production of textile products.*

1.3 Company/ Undertaking:

1.3.1 Manufacturer : *Recron (Malaysia) Sdn. Bhd
Level 7, 8, 9, Wisma Goldhill,
67, Jalan Raja Chulan,
50200 Kuala Lumpur,
MALAYSIA
Tel.: +603-2031 6000
Fax: +603-2031 5000*

*E-mail address of person responsible for the Safety Data Sheet:
tan.keksaan@recron.com*

1.3.2 Emergency telephone: *+6012-6708710 OR +6019-6511737
(24 x 7) Product Safety Manager*

1.4 REACH Only Representative *Attn: Mr James Searles
Steptoe & Johnson LLP
240 Avenue Louise, 1050 Brussels, Belgium
Tel: +3226260500, Fax: +3226260510
Email: jsearles@steptoe.com*

2. HAZARDS IDENTIFICATION

Hazard Codes: Not applicable

Risk phrases: Not applicable

Safety phrases: Not applicable

This product is not considered hazardous or toxic. The hazards if any, are associated with its processing. Fibre dust and spinnings fumes may represent a fire hazard at sufficient concentrations in presence of ignition sources.

3. COMPOSITION INFORMATION ON INGREDIENTS

3.1 Composition:

Chemical Identity	CAS No	EINECS/ ELINCS No	Concentration
Polymer (Polyethylene terephthalate)	25038-59-9	Not listed	> 92%
Additives (Titanium dioxide, colourants [optional])	-	-	< 4%
Spinnings & coning oil	-	-	< 4%
Hazardous ingredient			None

Safety data sheet

(According to Regulation (EC) 1907/2006)

 **Recron**
Malaysia Sdn Bhd
Member Reliance Group

Recron Polyester Texturised Yarn

4. FIRST AID MEASURES

- 4.1 Inhalation:** Inhalation of dust and finish decomposition products should be avoided by hood suction and fresh air ventilation. In case of coughing or other symptoms the person should seek fresh air and if necessary, see a physician.
- 4.2 Skin contact:** Wash with soap and water. If irritation develops, consult a physician.
- 4.3 Eye contact:** The eyes should be washed immediately with plenty of water. If irritation continues, consult a physician.
- 4.4 Ingestion:** Do not induce vomiting. Call in a physician and show him this data sheet.

5. FIRE-FIGHTING MEASURES

- 5.1 Burning behaviour:**
- | | |
|----------------------------|--|
| Flammable class: | Not determined |
| Flash point: | Not applicable. Product burns in fire. |
| Self-ignition temperature: | 515 °C DIN 51794 |
| Decomposition temperature: | > 300 °C |
- 5.2 Suitable extinguishing media:** Dry Chemical Powder, CO₂ or Water Spray (see 5.3 below)
- 5.3 Extinguishing media which must not be used for safety reasons:** Do not use water, if fire is caused by an electrical short circuit.
- 5.4 Special exposure hazards in a fire:** Low fire hazard. Fibre dust & fumes may represent a fire hazard at sufficient concentrations. On complete combustion, the major products formed are carbon dioxide & water. Remove ignition sources. Beware of electrostatic charges.
- 5.5 Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus, protective clothing and headgear to prevent contact with skin & eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Use normal personal protection.
- Environmental precautions:** In case of accidental spills, do not allow entering drains and waterways. When picked up, treat material as prescribed under section 13 (Disposal considerations).
- Methods for cleaning up:** Clean up by vacuuming, physical picking or mechanical means.
If cleaning up involves the use of water, the wastewater should be given the appropriate treatment in an effluent treatment plant, in line with local regulations.

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron Polyester Texturised Yarn

7. HANDLING AND STORAGE

7.1 Handling:

Normal handling and processing does not require special technical protective measures. Avoid formation of dust.

Accumulation of fibre dust may represent at sufficient concentrations a fire and explosion hazard. Remove ignition sources. Beware of electrostatic charges.

If subsequent processing involves the use of water, the wastewater should be given the appropriate treatment in an effluent treatment plant, in line with local regulations.

7.2 Storage:

Store at ambient temperatures.

Bobbins/ beams/ cartons must be stored in line with existing provisions. Existing fire protection measures have to be followed.

Do not store near flame, ignition sources, direct sunlight or incompatible materials. Maintain good housekeeping to control

8. EXPOSURE CONTROLS PERSONAL PROTECTION

8.1 Exposure limit values:

Comply with national occupational threshold values for dust.

According to TRGS 900 (Germany) there are two values:

- a) 3 mg/m³ - for fine dust
- b) 10 mg/m³ - for coarse dust

8.2 Exposure controls:

Avoid accumulation of and contact with fibre dust and finish decomposition products by hood suction, sufficient fresh air

a) Respiratory protection:	No special measures required, except for fire or insufficient hood suction / fresh air supply (see 4 and 5).
b) Hand protection:	Protective gloves are required while cutting carton straps or fibre waste.
c) Eye protection:	Wear safety glasses (e.g. especially while cutting bale or carton straps).
d) Skin protection:	No special measures required. Fibres that are processed at high speeds may cause abrasions or cuts. Appropriate protective

8.2.2 Environmental controls:

exposure

Exhausted fibre dust and finish decomposition products shall be kept back efficiently by adequate filter systems.

Safety data sheet

(According to Regulation (EC) 1907/2006)

 **Recron**
Malaysia Sdn Bhd
Member Reliance Group

Recron Polyester Texturised Yarn

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General Information

Appearance	Form: Bobbin, Beam
Colour	Raw-white, white or dyed
Odour	Odourless

9.2 Important health, safety and environmental information

pH	Not applicable
Melting point/range	250 - 260 °C
Flash point	Data not available
Flammability	Data not available
Explosive properties	Data not available
Oxidising properties	None
Vapour pressure	Not applicable
Relative density	1.3 - 1.4 g/cm ³
Solubility	Insoluble in common solvents.
Water solubility	Insoluble
Partition coefficient:	Not applicable
Viscosity	Not applicable
Vapour density	Not applicable
Evaporation rate	Not applicable

10. STABILITY AND REACTIVITY

- 10.1 Conditions to avoid:** Material is stable under normal conditions.
Temperatures above 300 °C lead to thermal decomposition (see also 5.6)
- 10.2 Materials to avoid:** Strong oxidation agents as well as strong acids and caustic will decompose polyester.
Acetic anhydride, acetone, aniline, benzene, chloroform, chromic acid, cyclohexanone, dimethylformamide, dioxan, ethyl acetate, methyl ethyl ketone, methylene chloride, phenol, tetrahydrofuran, trichloroethylene, triethanolamine, caustic soda.
- 10.3 Hazardous decomposition products:** Above the decomposition temperature, the major volatiles will be terephthalic acid, oligomers of PET, carbon dioxide, carbon monoxide, acetaldehyde, and low molecular weight alcohols/ aldehydes.
If heated to 150-250 °C during processing, the fibre lubricants can degrade and generate off gases, which may contain small amounts of chemicals such as aldehydes, alcohols, acetic acid, acetone, etc.
We are not aware of chemicals such as these reaching concentrations that present a serious health hazard. However, information on toxic effects and recommended exposure limits of these and other chemicals can be found in the most recent edition of the ACGIH documentation of threshold limit values.
When Polyester Filament Yarn is burned, no unusual combustion gases have been observed, and its combustion products are similar to those of other organic materials composed of the same elements.

Safety data sheet

(According to Regulation (EC) 1907/2006)

 **Recron**
Malaysia Sdn Bhd
Member Reliance Group

Recron Polyester Texturised Yarn

11. TOXICOLOGICAL INFORMATION

11.1	Acute toxicity	Low oral toxicity
11.2	Inhalation	Low acute toxicity. Dusts and vapours or fumes evolved during thermal processing may cause irritation to the respiratory system.
11.3	Ingestion	Data not available
11.4	Skin irritation	No evidence of irritant effect from normal handling and use.
11.5	Eye irritation	Dust and fumes generated during processing may have irritant effect on eyes. Permanent damage is unlikely.

Recron Polyester Filament Yarn is a non-toxic man-made fibre. Proper use has not been associated with any special hazard or any detrimental effects on health. It meets the requirements of Oeko-Tex standard 100 (Class-1), indicating the absence of harmful substances.

12. ECOLOGICAL INFORMATION

12.1	Eco-toxicity:	Low toxic to aquatic organisms. The fibre product can be separated out mechanically. Some finish components may vaporize or decompose at temperatures above 130 °C. If subsequent processing involves the use of water, the wastewater should be given the appropriate treatment in a purifying plant, in line with local regulations.
12.2	Mobility:	The product is insoluble in water. Due to their negligible solubility in water and high molecular weight, they are expected to have a low BOD and will not cause oxygen depletion in aquatic systems.
12.3	Persistence and degradability:	The product is non-biodegradable in soil.
12.4	Bio accumulative potential:	They are expected to be non-biodegradable and unlikely to bio-concentrate.
12.5	Other adverse effects:	Unlikely to affect biological treatment processes.

13. DISPOSAL CONSIDERATIONS

Disposal of Polyester product does not pose any specific danger.

It is recommended that Polyester Filament yarns & waste be recycled. (Recycling has commercial value too).

If recycling is not possible, Polyester waste yarns & waste can be disposed of in a suitable refuse installation or incinerated subject to local regulations.

14. TRANSPORT INFORMATION

14.1	UN number:	Not applicable
14.2	Class/ Packing group:	Not restricted
14.3	Marine pollutant:	None
14.4	International Transport Regulations:	Not classified as dangerous for transport
14.5	Road / Rail (ADR / RID):	Not restricted
14.6	Sea (IMDG):	Not restricted
14.7	Air (ICAO / IATA):	Not restricted

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron Polyester Texturised Yarn

15. REGULATORY INFORMATION

Recron Polyester products do not require hazard warning labels in accordance with EC directives.

Risk phrase(s): Not applicable

Safety phrase(s): Not applicable

16. OTHER INFORMATION

16.1 Relevant R-phrases Not applicable

16.2 Recommended restrictions on use:

This safety data sheet is provided for the products and their applications as specified in Section 1. The safety data sheet is not written with the individual end-user in mind.

It is recommended that supplementary information be requested if an unusual application of these products is intended.

Consult the manufacturer if the product(s) is to be used for special applications (such as, but not limited to, the food, hygienic, medical or surgical sectors) or for new end-uses.

16.3 Further Information:

Recron® Polyester Textured Yarn is an article made of man made fibres and is not subject to **European Regulation (EC) 1907/2006** on registration, evaluation and authorization of chemical substances (**REACH**). Safety Data Sheets or Chemical Safety Reports according to *Art. 31* of this regulation are therefore not required.

This data sheet was established following *Annex II* of this regulation. The raw materials and auxiliaries used for the manufacturing of **Recron® Polyester Texturised Yarn** are predominantly concerned by this regulation. Recron will track the status of the registration and evaluation of these materials.

16.4 Disclaimer:

This Safety Data Sheet and the health, safety and environmental information it contains are intended to provide a summary of our knowledge and guidance regarding use of the designated Product. Its contents are offered in good faith as accurate and complete as of the date specified below, but without guarantee. The data herein applies only to the Product sold by Recron (Malaysia) Sdn. Bhd. and not to products sold by others. It relates only to the Product and does not relate to its use in combination with any other product or material or in any process.

Local laws and regulations and conditions of use and suitability of the product for particular uses are beyond the control of Recron; all risks of use, storage, handling, transportation and disposal of the Product are therefore assumed by the user and Recron expressly disclaims all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the Product. Recron shall not be responsible for any damage or injury resulting from abnormal use of the Product, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the Product.

Appropriate warnings and safe handling procedures should be provided to all handlers and users. In the case of a user in the European Union, as per Article 34 of REACH Regulation (EC) No. 1907/2006, user shall communicate to Recron any new information on hazardous properties of the Product and/or new information relevant to risk management measures for the identified uses.

Alteration or re-publication of this document in whole or part is strictly prohibited.